



Installation Instructions: FLT and FLHT 1983-1996 One-Piece Ultra Touring Seat

A. Baseplate Features

One-piece ultra touring seats are constructed on extra rugged, triple layered fiberglass. The baseplate is slotted in the middle to allow for the use of a frame-mounted driver backrest.



1991-1996 baseplate shown

Note: 1983-1990 Mustang FL seats mount to the stock handrail. If the handrail is removed, the fender bracket #78007 is needed in its place.

B. Mounting of Mustang seat

1983-1990

1. Remove nuts and washers from studs on baseplate of seat.
2. Engage nose of seat with bracket on frame.
3. Align rear studs with holes in stock handrail or bracket #78007.
4. Fasten with supplied washers and nuts.

1991-1996

1. Install supplied chromed triangle "Z" bracket onto seat baseplate and tighten screws.
2. Engage tab on frame of bike into receiver at nose of seat.
3. Firmly push seat forward to meet chrome dash panel.
4. Align slot in "Z" bracket with threaded hole in tourpak platform.
5. Secure seat with stock screw.

Installation Instructions:
FLT and FLHT 1983-1996
One-Piece Ultra Touring Seat

Enjoy the comfort of your new Mustang seat.



Seat #75565 shown on bike along with
wrap-around backrest #75317

These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "[Support](#)".

Ref: part #'s 75524, 75525, 75554, 75555, 75564, 75565, 75571, 75572, 75575, 75576, 76050, 76051, 76052, 76053