

www.GRAVESPORT.com

Tel (818) 902-1942 Fax (818) 902-3821

7629 Densmore Avenue Van Nuys, CA 91406

EXY-11FZ8-CBSC

Cat Back Slip-On Exhaust System Yamaha FZ-8 (2011)

PARTS LIST

•	Silencer	1	Hanger Strap w/Rubber Heat Shield	1
•	Tail Pipe	1	Bolt, 8 x 16mm Hex Head	1
•	Clamp	1	Spring	1

<><<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>

Be sure the motorcycle is cooled down and safe to work on.

- 1. Remove the stock exhaust muffler.
- 2. Remove the muffler bracket from the inside of the passenger foot rest.
- 3. Place the clamped end of the tailpipe on the stock mid-pipe, leaving loose until alignment is complete.
- 4. Slide the silencer onto the tail-pipe making sure all the slip fits are fully engaged. Mount the spring.
- 5. Place the hanger strap and rubber heat shield around the silencer using the supplied 8 x 16mm hex bolt. Mount the silencer to the inside of the passenger foot rest utilizing the stock muffler bracket hole.
- 6. Check all alignments and tighten the clamp on the mid-pipe.
- 7. Wipe all dirt, grease and fingerprints from the silencer and pipes before starting the engine.