

5420 DANIELS STREET STE A CHINO CALIE 01710 / (800)634-0166 / (000)628-4722 / EACSIMILE / (000)591-2108

www.yoshimura-rd.com

R-K5720-K 2010-2013 BMW S1000RR Oil Filler Plug



NO.	DESCRIPTION	QTY	PART #
1	Oil Filler Plug	1	R-K5720

Instructions:

- 1. Remove stock oil filler plug.
- 2. Remove stock rubber o-ring from oil filler plug and install on Yoshimura oil filler plug.
- 3. Install Yoshimura oil filler plug.

 Torque to 7.4 lb-ft (10 Nm).

If safety wire is required, loop safety wire through the holed drilled in the plug to secure location.

197 YOSHIMURA

EA20 DANIEL C CTREET CTE A CHIMO CALLE 04740 / (900)(224 0466 / (000)(229 4722 - EACCIMILE (000)(504 2400

www.yoshimura-rd.com

R-K5720-K 2010-2013 BMW S1000RR Oil Filler Plug



NO.	DESCRIPTION	QTY	PART #
1	Oil Filler Plug	1	R-K5720

Instructions:

- 1. Remove stock oil filler plug.
- 2. Remove stock rubber o-ring from oil filler plug and install on Yoshimura oil filler plug.
- 3. Install Yoshimura oil filler plug.

 Torque to 7.4 lb-ft (10 Nm).

If safety wire is required, loop safety wire through the holed drilled in the plug to secure location.

E B 17 YOSHIMURA

ON DANIEL & STREET STE A. CHINO CALIE 04740 . (200) 224 0425 . (200) 229 4722 . EACSIMILE (200) 24 0425

www.yoshimura-rd.com

R-K5720-K 2010-2013 BMW S1000RR Oil Filler Plug



NO.	DESCRIPTION	QTY	PART #
1	Oil Filler Plug	1	R-K5720

Instructions:

- 1. Remove stock oil filler plug.
- 2. Remove stock rubber o-ring from oil filler plug and install on Yoshimura oil filler plug.
- 3. Install Yoshimura oil filler plug.

 Torque to 7.4 lb-ft (10 Nm).

If safety wire is required, loop safety wire through the holed drilled in the plug to secure location.

EDA YOSHIMURA

RESEARCH&DEVELOPMENT OF AMERICA, INC.

www.yoshimura-rd.com

R-K5720-K 2010-2013 BMW S1000RR Oil Filler Plug



NO.	DESCRIPTION	QTY	PART #
1	Oil Filler Plug	1	R-K5720

Instructions:

- 1. Remove stock oil filler plug.
- 2. Remove stock rubber o-ring from oil filler plug and install on Yoshimura oil filler plug.
- Install Yoshimura oil filler plug. Torque to 7.4 lb-ft (10 Nm).

If safety wire is required, loop safety wire through the holed drilled in the plug to secure location.