

## www.GRAVESPORT.com

Tel (818) 902-1942 Fax (818) 902-3821

7629 Densmore Avenue Van Nuys, CA 91406


## **EXK-11ZX1-CETCL**

## Slip-On Exhaust System Kawasaki ZX-10R 2011

## **PARTS LIST**

Tail Pipe	1	Hanger Strap & Rubber	1	8mm x 25mm Flanged Bolt	1
Silencer	1	Barrel Clamp	1	8mm x 16mm Flanged Bolts	2
Hanger Bracket	1	8mm Flanged Nut	1	Spring	1
Lambda Bung & Washer	1				

- 1) Remove lower bodywork. Disconnect the servo cables and remove the stock catalytic converter and muffler.
- 2) For ease of installation, remove the right side foot peg bracket. Note which position the bracket is in for future reference.
- 3) Mount the silencer hanger bracket on the inside of the frame using the adjustable foot peg mounting holes and the supplied 8 x 16 mm flanged bolts. NOTE: If your foot peg is mounted in the lower position, mount the silencer bracket using the upper bolt holes as shown in the photo.



- 4) Slide the supplied barrel clamp around the tailpipe and fit the tailpipe onto the stock head pipe assembly.
- 5) Install the silencer onto the tail pipe. Attach the supplied spring to the spring tabs.
- 6) Wrap the silencer hanger strap and rubber heat guard around the silencer and mount to the hanger bracket using the 8 x 25mm flanged bolt and 8mm flanged nut. Before tightening to 14 ft lbs/20Nm check all clearances and fitment. Tighten the barrel clamp at the head pipe assembly.
- 7) Replace the foot peg and bodywork checking for clearances and fitment.
- 8) Before starting your motorcycle be sure to clean all fingerprints, oil and debris from the pipes and silencer to prevent permanent staining.