



MOUNTING SUGGESTIONS:

Harley-Davidson FXSB Breakout 2013-2014 One-piece Seat

Hardware: Stock 1/4" -20 Rear fender Screw

Tools needed: Phillips screwdriver

Removal of Stock Seat:

1. Remove the rear 1/4"-20 fender screw with a Phillips screwdriver and set it aside. The stock rear fender screw will be used to attach your new Mustang seat.

2. Slide the rear seat back and out of the hand strap. (Fig. 1)



Fig. 1

3. Loosen the two thumb screws holding the driver in place.

4. Carefully lift the back of the driver's seat up and back to disengage the front bracket and remove the seat.

5. Remove the hand strap and reinstall the two thumb screws.

Installation of Mustang Seat:

1. Engage the nose bracket into the frame at the base of the fuel tank, just like the stock seat.

2. Secure the seat's rear bracket to the fender with the stock 1/4"-20 fender screw to complete the installation process.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 76780, 76781

You are cordially invited to
— Tour the Mustang Factory —

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.