



# .....Mounting Suggestions Harley-Davidson® Dyna Glide & .....Dyna Wide Glide 1996- 2005 .....One-Piece Seat

## Tools Required:

- Phillips Screwdriver

## Hardware:

- Stock Rear Fender Screw
- Chrome Mounting Bracket (Included)



*Bracket shown in Dyna Wide Glide Position*

## **Baseplate Features:**

All one-piece formed steel baseplates have two sets of holes for the supplied chrome bracket to bolt into. The first set of holes closest to the rear of the seat is for all Dyna Wide Glide models and the second set of holes is for all Dyna Glide models. Once in place the slotted chrome bracket aligns with the threaded hole in the fender.

## **Removal of Stock Seat**

1. Remove rear fender screw and set aside. The stock rear fender screw will be used to attach your new Mustang One-Piece Seat.
2. If applicable, remove seat strap.
3. Slide seat back and lift up.

## **Mounting of Mustang Seat**

1. Secure rear bracket to baseplate of passenger seat with supplied screws. Use the set of holes closest to the rear of the seat for all Dyna Wide Glide models and second set of holes for all Dyna Glide models. (Fig. I)
2. Engage nose bracket under welded frame tab.
3. Align chrome rear tab with threaded mount in fender.
4. Push seat down and secure with stock fender screw to complete the installation process.

Fig. I



*Bracket shown in Dyna Wide Glide Position*

**Enjoy the Comfort of your new Mustang Seat!**



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at [www.mustangseats.com](http://www.mustangseats.com).

For care and maintenance of our seats, please go to our website under "Support".

Ref part #'s 75582, 75583, 75649, 75150, 75439, 75143, 75532, 75145, 76387, 76392, 75533, 75134, 75746, 75139, 75530, 75405, 75109, 75536, 75111, 75415, 75531, 75125, 75425