



## Part # FE102

***Honda CBR600RR 13-14***

### Fender Eliminator Kit Contents

Description	Qty.		Description	Qty.
Fender Brackets	3		6x16 Bolt	6
6x15mm Washer	6		6x12 Bolt	2
6mm Locknut	6		Flashing Spacer	2
6x12mm Washer	10		Frame Spacer	2
6x35 Bolt	2		Zip Tie	1
9" Heat Shrink Tubing	1		Flashing Screw	2

**Make sure bike is turned off and cool to the touch before and during installation. It is highly recommended that the VORTEX fender Eliminator is installed by a certified technician. VORTEX is not responsible for any part of your motorcycle for any reason. If in any doubt please call us during installation at 800-440-3559.**

- Remove front and rear seat. Remove tail section body work.
- Remove rear pipe cover.
- Follow wires back from the OEM Fender and unplug the stock wires. Note: Identify the left and right hand turn signals and plate light.
- Remove the OEM Fender.
- Separate the OEM fender and remove the stock pipe flashing covers.
- Install the OEM flashing covers to the provided VORTEX left and right hand bracket.
- Mount lower OEM screw first
- There will be a gap between the upper flashing hole and the VORTEX bracket. Place the spacer in between the flashing cover and VORTEX bracket. The spacer will fit over the flashing cover extrusion. Mount the provided flashing screw.
- Install the rear pipe cover but leave the bolts loose.
- Remove exhaust sub frame and alignment bolt (alignment bolt is located in front of the brake light).
- Slide the flashing cover (with the VORTEX bracket mounted) onto the rear exhaust cover. Make sure the slot on the flashing cover slides onto the rear pipe cover track.
- On the right hand side, line the rear hole of the VORTEX fender bracket with the rear hole on the sub frame and install the 6x16 bolt with the 6x15 (larger 6mm washer) washer. Keep the bolt loose.
- Repeat step 12 on the left hand side

- On the right hand side, slide the spacer in between the frame and right side bracket. Install the 6x35 bolt with the 6x15 (larger 6mm washer) washer. **Tip:** Use a flash light to line the holes up when installing the bolt. You can maneuver the exhaust and exhaust bushing to line everything up.
- Tighten both fender bracket bolts.
- Repeat steps 14 and 15 on left hand side.
- Install exhaust alignment bolt.
- Tighten rear exhaust cover.
- Install the VORTEX plate bracket using the following hardware. Tip: install bolts and nuts diagonally one at a time. Torque down once all hardware has been installed.
  - 4 – 6x16mm bolts
  - 8 – 6x12 washers (smaller 6mm washer)
  - 4 – 6mm lock nuts
- Install marker and plate lights.
- Route the wires using the provided heat shrink tubing (tubing will shrink down to 1/4" with a proper heat gun) and zip tie as shown below.
- Install tail section and seats. Make sure all bolts are tightened to the proper torque specifications.