

## www.GRAVESPORT.com

Tel (818) 902-1942 Fax (818) 902-3821

7629 Densmore Avenue Van Nuys, CA 91406

## EXK-13ZX6-CBTx

Cat-Back Exhaust System Kawasaki ZX-6RR 2009-2013 Kawasaki ZX6R (636) 2013

## **PARTS LIST**

Silencer 10mm Lock Nut

<><<INSTALLATION OF THIS PRODUCT SHOULD BE PERFORMED BY A QUALIFIED TECHNICIAN >>>>
<><<<>PLEASE READ INSTRUCTIONS CAREFULLY BEFORE BEGINNING INSTALLATION >>>>>>

- 1) Remove lower bodywork heat shield bodywork pieces, both over the catalytic converter and the sound chamber (3 bolts).
- 2) Remove the rear passenger seat.
- 3) Remover the tank/ frame body work pieces on both side (1 bolt each side) and then remove the riders seat (2 bolts).
- 4) Remove the servo cable retaining clip (PHOTO 1). Remove bolt holding the Servo Cam with a T25 Tamper-Resistant Torx. Disconnect the servo cables from the cam.




PHOTO 1

- 5) Loosen clamp behind the sound chamber. Remove hanger bolt on the right rear passenger peg and pull servo cables through the frame to remove the stock silencer.
- 6) Loosen the clamp behind the catalytic converter. Remove the hanger bolt for the rear chamber and keep for re-use. Remove the rear sound chamber but retain the hose clamp.
- 7) Install the silencer onto the catalytic converter till it stops. Line up the mounting hole to the frame and use stock bolt from the rear sound chamber. Use provided lock nut on the bolt and torque to 22 ft. lbs./ 30Nm. Tighten the hose clamp.
- 8) Replace the bodywork and seats checking for clearances and fitment.
- 9) Before starting your motorcycle be sure to clean all fingerprints, oil and debris from the pipes and silencer to prevent permanent staining.