

INSTALLATION INSTRUCTIONS

Winch Mount

Part Number: 101688
Application: John Deere

GENERAL SAFETY PRECAUTIONS

Your safety, and the safety of others, is very important. To help you make informed decisions about safety, we have provided installation and operating instructions and other information on labels and in this guide. This information alerts you to potential hazards that could hurt you or others. It is not possible to warn you about all potential hazards associated with this product, you must use your own good judgment.

CARELESS INSTALLATION AND OPERATION CAN RESULT IN SERIOUS INJURY OR EQUIPMENT DAMAGE. READ AND UNDERSTAND ALL SAFETY PRECAUTIONS AND OPERATING INSTRUCTIONS BEFORE INSTALLING AND OPERATING THIS PRODUCT.

This guide identifies potential hazards and has important safety messages that help you and others avoid personal injury or death. WARNING and CAUTION are signal words that identify the level of hazard. These signal words mean:

▲WARNING signals a hazard that could cause serious injury or death, if you do not follow recommendations. **▲**CAUTION signals a hazard that may cause minor to moderate injury, if you do not follow recommendations.

This guide uses NOTICE to call attention to important mechanical information, and Note: to emphasize general information worthy of special attention.

A WARNING

IMPACT AND MOVING PARTS ENTANGLEMENT HAZARD

Failure to observe these instructions could lead to severe injury or death

- Always take time to fully read the Instructions and/or Operations Guide, and/or Basic Guide to Winching Techniques, in order to understand your winch and its operations.
- Always use extreme caution when drilling on any vehicle. Make sure that all fuel lines, brake lines, electrical wires, and other objects are not punctured or damaged when/if drilling on the vehicle. Thoroughly inspect the area to be drilled (on both sides of material) prior to drilling, and relocate any objects that may be damaged. Failure to inspect the area to be drilled may result in vehicle damage, electrical shock, fire or personal injury.
- · Always wear safety glasses when installing this kit. A drilling operation will cause flying metal chips. Flying chips can cause eye injury.
- · Always use extreme caution when cutting and trimming during fitting.
- Always remove jewelry and wear eye protection.
- **Never** lean over battery while making connections.
- **Never** route electrical cables:
 - o Across any sharp edges.
 - Through or near moving parts.
 - o Near parts that become hot.
- Always insulate and protect all exposed wiring and electrical terminals.
- Always install terminal boots as directed in installation instructions.
- Always use appropriate and adequate care in lifting components into place.
- Always insure components will remain secure during installation and operation.
- Always tighten all nuts and bolts securely, per the installation instructions.
- Always perform regular inspections and maintenance on the plow mechanism, fasteners, cable and related hardware.
- Always replace all worn or damaged parts before operating.
- Never operate this WARN product with damaged or missing parts.

Read installation and operating instructions thoroughly.

A CAUTION

MOVING PARTS ENTANGLEMENT HAZARD

Failure to observe these instructions could lead to minor or moderate injury

- Always take time to fully read and understand the installation and Operations Guide included with this product.
- **Never** operate this product if you are under 16 years of age.
- **Never** operate this product when under the influence of drugs, alcohol or medications.

Read installation and operating instructions thoroughly.

NOTICE

EQUIPMENT DAMAGE

- **Never** tow vehicle by attaching a tow bar to the eyelets on the bumper.
- Never attach tow bars directly to the bumper. Damage to bumper may occur. WARN bumpers are not designed to be used for flat towing. Consult with the manufacturer of your tow bar system for the proper vehicle tow bar brackets..

Read installation and operating instructions thoroughly.

TABLE OF CONTENTS

 Tools Required
 page 2

 Torque Specifications
 page 2

 Parts List
 page 2

 Installation
 page 3-4

 Maintenance/Care
 page 4

TOOLS REQUIRED

- Metric wrenches
- Metric sockets

TORQUE SPECIFICATIONS

Please use the recommended torque specifications when assembling this product unless otherwise specified in the instructions.


FASTENER SIZE 1/4" 5/16" 3/8" 7/16"	FASTENER TORQUE		FASTENER SIZE	FASTENER TORQUE	
	lb-ft	(N.m)		lb-ft	(N.m)
1/4"	8	(11)	M4	(2)	3
5/16"	17	(23)	M5	(4.5)	6
3/8"	30	(40)	М6	(7.5)	10
7/16"	48	(66)	М8	(18)	25
1/2"	74	(100)	M10	(37)	50
9/16"	106	(144)			
1/2" 9/16" 5/8" 3/4"	148	(200)			
3/4"	269	(364)			

PARTS LIST


PARTS LIST						
LINE ITEM	PART NUMBER	DESCRIPTION	QTY			
A1	101801	WINCH MOUNT	1			
	HAR	DWARE LIST				
LINE ITEM	PART NUMBER	DESCRIPTION	QTY			
B1	91165	FLANGED NYLOCK NUT	4			
B2	220026	FLAT WASHER	4			
В3	22528	M10 HEX HEAD BOLT	4			
B4	75599	M8 CAPSCREW	4			

INSTALLATION INSTRUCTIONS


- 1. Remove factory skid plate from vehicle.
- 2. Install fairlead to winch mount (A1) per winch kit instructions and using winch kit fairlead hardware.
- 3. Install one of the M10 Hex Head Bolt in front passenger side mounting bracket hole (This will ease the winch mounting.).



4. Mount winch, using supplied M8 capscrews (B4). NOTE: You will use the four supplied washers for AXON winch only.



- 5. Insert winch/mount assembly in vehicle position.
- 6. Install the last three M10 hex head bolts (B3) through winch mount and vehicle mount plate. Secure ALL four bolts with flanged nylock nut (B1).



- 7. Tighten all hardware.
- 8. Complete your winch wiring per your winch installation instructions.
- 9. Your installation is now complete.



MAINTENANCE / CARE

- 1. Inspect all parts on the winch, winch mount, and related hardware prior to each use. Replace all hardware that appears rusted or deformed.
- 2. Inspect all nuts and bolts on the winch, winch mount and related hardware prior to each use. Tighten all nuts that appear to be loose. Stripped, fractured, or bent bolts or nuts need to be replaced.
- 3. Check all cables prior to use. Replace cables that look worn or frayed.
- 4. Check all moving or rotating parts. Remove debris that may inhibit the part from moving freely.

WARN INDUSTRIES, INC. 12900 S.E. Capps Road, Clackamas, OR USA 97015-8903, 1-503-722-1200, FAX: 1-503-722-3000 Customer Service: 1-800-543-9276

Dealer Locator Service: 1-800-910-1122 International Fax: 1-503-722-3005