

## Designed to work with the following winches:

- **KFI:** ST17 / A2000 / A2500-R2 / A3000 / U45-R2 / U45w-R2 / SE25 / SE35 / SE45-R2 / SE45w-R2
- **KFI:** AS-50 / AS-50w
- **WARN:** VRX 25 / VRX 25-S / VRX 35 / VRX 35-S / VRX 45 / VRX 45-S
- **WARN:** AXON 35 / AXON 35-S / AXON 45RC / AXON 45 / AXON 45-S / AXON 55 / AXON 55-S
- **WARN:** A2000 / A2500 / U2500 / 1.5ci / 2.5ci / 2.5ce / 3.0ci / 3.0ce / 3.0s
- **WARN:** RT15 / RT25 / RT30 / XT15 / XT25 / XT30
- **WARN:** RT40 / XT40
- **WARN:** Vantage 2000-4000lb
- **WARN:** ProVantage 2500-4500lbs
- **BADLAND:** Standard Winches
- **BADLAND:** WIDE Winches
- **CHAMPION:** Standard Winches
- **CHAMPION:** WIDE Winches
- **KEEPER CORP. TRAKKER:** KT2500 / KT3000 / KT2500C / KT3000C / KT4000 / KT4000C
- **MILE MARKER:** PE2.5 / PE 3.5 / VMX2.5 / PE2000 / PE3000 / PE2500 / PE3500 / PE5000
- **QUADBOSS:** RP25 / RP35
- **RAMSEY:** ATV2500 / ATV3000
- **SMITTYBILT:** XRC 3.0 / XRC 4.0
- **SUPERWINCH:** Terra25 / Terra35 / Terra 45 / A3500 / LT2000 / LT2500 / LT3000 / LT4000ATV / LT4000UTV
- **TRAVELLER:** 1078311
- **VENOM:** 2000 / 2500 / 3000 / 3500 / 4000 / 4500 / 5000 (Hardcore Series)
  - All with 3.00" x 4.875" bolt pattern mount-up
  - All with 3.00" x 6.600" bolt pattern mount-up
- **XGEAR:** X3000 / X4000
  - 4-Hole Standard (3.00" x 4.875" bolt pattern)
- **Many others with the below standard mounting patterns:**
  - 4-Hole (3.00" x 4.875" bolt pattern with rollers that are 4.875" bolt pattern)
  - 4-Hole WIDE (3.00" x 6.60" bolt pattern with rollers that are 6.600" or 6.000" bolt pattern)