



700 S. Hathaway St. Unit E
Banning, CA. 92220
web: <http://www.imsproducts.com>
Information: (951) 653-7720

HONDA:
CR GENERIC KIT

CR / CRF
CR125 / CR250
CRF250R/X & CRF450R/X

FUEL TANKS:

TANK ID: IMS Part #'S

CR-14: 112227 / 212227

CR-15: 112230 / 212230

CR-16: 112231 / 212231

CR-20: 112238 / 212238

CR-24: 112242 / 212242

PARTS LIST

- (1) Fuel Tank
- *(1) Gas Cap-322100-BLK
- *(1) SEAL-322101
- (*Excluded on Dry-Break*)**
- (1) 6X25mm Flat Washer
(MTP-9028106025)
- (2) 6x12mm Big Flange Bolts
(MTP-5369106012)
- (1) 6x25mm Flange Head Bolt
(MTP-1189106025)
- (1) CR-2000 Front Bracket
(BRK-IMS-CR2000)
- (1) GROMMET
(MCM-9307K42)
- (1) SPACER
(BRK-SP1006X8FK)

STOCK ITEMS TO USE

- Petcock & Screws
- Fuel Lines
- Vent Hose

10% OFF

YOUR NEXT PURCHASE

Date _____

Address _____

Phone _____

700 S. Hathaway St. Unit E
Banning, CA. 92220
Phone (951) 653-7720

WARNING!

Clean Tank Interior Thoroughly Before Installation. Install This Fuel Tank **ONLY** In a Well Ventilated Area, As Gasoline Fumes Are **EXTREMELY Dangerous**. **DO NOT START OR OPERATE THE VEHICLE IF THERE ARE ANY FUEL LEAKS!** IMS Recommends That a Licensed Mechanic Do Installation. Read All Instructions First Before Beginning Installation.

TANK REMOVAL

Drain the fuel from your stock tank into approved gasoline container. Remove the seat, rubber tank strap and the fuel line from the petcock. Remove the shrouds and unbolt the mount at the front of the tank. Pick the tank up off the bike and remove the petcock and remaining hardware.

TANK INSTALLATION

Mount your stock petcock, seat button and rubber strap stay to the IMS tank. Next attach the **IMS** mounting bracket to frame where OEM tank front mount fastened just below steering head. Use the supplied 6 x 25mm flange head bolt with 1/4" x 1" flat washer.

Place the **IMS** tank on the frame and attach it to the mounting bracket with the two 6 x 12mm bolts. If you turn the handlebars to the stop it will give you a straight shot to the bolts for a tee handle etc. Reattach the shrouds using the stock hardware being sure to leave the bolts loose until all bolts are started before you tighten them. Install the tank strap and seat. Connect the fuel line to the petcock and place your vent line on the **IMS** gas cap.

Be sure that the tank is mounted securely and does not bind or in any way inhibit the controls or function of the vehicle. Ensure that there are no sharp objects that rub against the tank that may eventually puncture the tank. Turn the petcock to the closed position. Fill the fuel tank & **CHECK FOR ANY LEAKS AND ENJOY YOUR RIDE!!**

"FOR COMPETITION USE ONLY"

**"Legal in California ONLY for racing vehicles
which may never be used upon a highway."**

DISCLAIMER:

Due to uncontrolled variables in the manufacturing process of rotationally molded fuel tanks, the fuel tank may vary in size and shape by up to 7% of the manufacturer's original listed capacity