



GEN 2 OFFSET DRINK MOUNT FOR ARMRESTS

- WARNING** This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.
- CAUTION** This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.
- ATTENTION** This indication alerts you to the fact that if you ignore this detail you will affect the performance or functionality of the product.

All Ciro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation. Read completely and understand the instructions prior to starting installation.

NOTE: Ciro products are designed and manufactured under very strict quality control. Ciro warrants that products sold to the original purchaser shall be free from any defects in materials and workmanship for a period of 3 (three) years from the date of purchase, and a limited lifetime warranty against LED failure. Ciro will have no obligation if the customer cannot show proof of purchase. Warranty will not be granted unless the part is properly installed, unmodified and maintained. Ciro will not be liable for any consequential and incidental damages, including labor, or non-Ciro products. Please visit Ciro3d.com for our complete warranty policy.

Included Items:



Installation Instructions:

1. Park on a level surface and shut off motorcycle. Ensure the engine has time to cool before installation. Protect painted surfaces to prevent accidental damage to motorcycle.
2. Remove plug from armrest on side you want to install mount.
3. Decide if you want the mount to rotate freely or have stiffer resistance to wind or other forces. For a stiffer mount install the O ring in the channel shown above.

NOTE: Be aware that the mount with the O ring installed may turn over the drink holder if the trunk is opened.

4. With the collet nut from your drink holder put over the back of the mount with the threads facing out, place the mount into the hole with the slot facing up. Push the mount in until it stops and rotate either way 180 degrees. Fig. 1
5. To install drink holder refer to enclosed instructions with the accessory. Fig. 2

